

Cable HT underground galvanised U-series

This underground cable is used to carry the electricity from the energizer to the electric fence in a safe and insulated manner. It can also be used to carry the electricity under gates to the next section of fence.

This underground cable is suitable for use with galvanised wires, aluminium wires and all poly wires, poly ropes and poly tapes.



Features

- Heavy duty design for harsh environments
- 1.6 mm diameter inner conductor wire for shorter cable runs
- 2.5 mm diameter inner conductor wire for longer cable runs and larger fences.

Specifications:

- Solid heavy galvanised inner wire conductor
- 1.6 mm wire (98 Ohms/km)
- 2.5 mm wire (36 Ohms/km)
- Double insulated UV stabilised outer and inner sheaths

<https://www.nemtek.co.za/commercialsecurity/Cables-Connectors-and-Accessories/cable-ht-undergate.aspx>

Stock Code	Name	Description
AH-UC1.6/100	Cable HT underground galvanised U-series	HT Underground Cable 1.6mm - 100m
AH-UC1.6/25	Cable HT underground galvanised U-series	HT Underground Cable 1.6mm - 25m
AH-UC1.6/50	Cable HT underground galvanised U-series	HT Underground Cable 1.6mm - 50m
AH-UC2.5/100	Cable HT underground galvanised U-series	HT Underground Cable 2.5mm - 100m
AH-UC2.5/200	Cable HT underground galvanised U-series	HT Underground Cable 2.5mm - 200m
AH-UC2.5/25	Cable HT underground galvanised U-series	HT Underground Cable 2.5mm - 25m
AH-UC2.5/50	Cable HT underground galvanised U-series	HT Underground Cable 2.5mm - 50m
AH-UC2.5/500	Cable HT underground galvanised U-series	HT Underground Cable 2.5mm - 500m